

X-VAC TRAILER SPECIFICATIONS

General specifications:

- 500 or 800 gallon debris capacity
- 325 or 425 gallon water capacity Stainless steel water tanks
- 2 1/2" water fill hook-up
- 60.6 hp Kubota diesel engine
- High temperature/low oil shutdown on engine for safety and longevity
- User-friendly controls located on the curb-side for safe operation
- Roots positive displacement blower capable of : 758 cfm, 16" Hg vacuum 668 cfm, 27" Hg vacuum
- Manual vacuum breaker for safety and blower protection
- Water pump capable of 4 gpm 4000 psi
- Low water level shutdown
- Easy winterization hook-up to protect water pump and hoses
- 8.7 gpm gear-driven hydraulic pump mounted on engine
- Operate blower and water pump independently or simultaneously
- 55° dump angle on debris tank
- Manually operated full open rear door (hydraulically operated optional)
- Upper and lower sight glasses on rear door
- 6" gate valve on rear door
- Wet and dry vacuum capability
- Dry filter with centrifugal inlet
- Filter cleaning without removal
- Rugged 12,000 GVW trailer built to heavy duty construction specifications (14,000 GVW trailer for use with the larger X800)
- Balanced trailer layout to maintain even weight distribution
- Tool/accessory holders
- Dry weight = 5,500 lbs (model X500)
- Dry weight = 6,300 lbs (model X800)
- Overall length = 20' 6" (model X500)
- Overall height = 7' (model X500)
- Overall height = 7' 11" (model X800)
- Overall width = 102"
- 12 month limited warranty

Optional equipment available:

- Automatic high-level shutdown
- Remote vacuum-breaker control
- Internal tank flush heads
- Radio frequency level probe
- Hydraulic tool circuit
- Hydraulic controlled boom w/360° rotation
- Hydraulic controlled rear door
- Wireless remote control



A Product of Hi-Vac® Corporation

117 Industry Road
Marietta, OH 45750
Phone: 740-374-2306
Fax: 740-374-5447
E-mail: sales@hi-vac.com
Web: www.x-vac.com